



DVR



DMR-1622AUV DMR-1622ARV

16-Ch. Triplex M-JPEG/MPEG-4 DVR

Features

- Triplex Operation Mode
- M-JPEG / MPEG-4 Compression
- 3 Video Outputs
- 4 Looping Outputs
- 720 x 480 Monitoring Resolution
- 120(100) fps of Live-view Display
- Half D1 Res. with Max. 60(50) fps of Recording Speed
- Full Screen & 4 Screen Split
- Support 2 x SATA HDD
- Support VGA Output
- Motion Detection
- 8 Alarm Inputs / 1 Alarm Output
- USB Built-in
- CD-RW Built-in(DMR-1622ARV)
- DC 12V 5A
- Support IE Browser for remote Monitoring

Specification

Model		DMR-1622AUV	DMR-1622ARV
Video	Input	16-ch. Video Inputs ; 1.0 Vp-p, 75 Ohm (BNC TYPE)	
	Output	2 x Video Outputs (BNC) ; 1 x S-VHS Output; 1 x VGA Output	
Monitoring	Display Mode	Full Screen, 4 Screen, 9 Screen, 16 Screen, Split	
	Resolution	NTSC: 720(H) X 480(V) / PAL: 720(H) X 576(V)	
	Sequence	Available	
	Camera Adjustment	Available	
Record / Playback	Recording Resolution	NTSC: 640(H) X 224(V) / PAL: 640(H) X 272(V)	
	Recording Rate	Half D1: 60(50)fps , CIF: 120(100)fps	
	Storage Capacity	SATA HDD Interface x 2	
	Compression	MJPEG / MPEG-4	
	Record Mode	Continue / Motion Detect / Alarm / Schedule	
	Motion Detect	5 Sensitivity Level Adjustable	
	Search Mode	Time Date / Event	
Others	Backup	USB / Network	USB / CD-RW / Network
	Remote Controller	Yes	
	Alarm Input	16 Alarm In	
	Relay Output	1 Alarm Out	
	Audio	1ch Audio In / 1ch Audio Out	
	Network	Support TCP/IP	
	Mouse	Support PS2 mouse	
	Auto Record	Yes	
	Setting	Plug & Play	
Mechanics	VGA	Support 1024*768, 1280*1024	
	Operation Temperature	0°C ~ 60°C (32°F~140°F)	
	Operation Humidity	Less than 90%	
	Dimension	380mm X 290mm X 70mm	
	Weight (N.W)	3.3 kg	
Power Supply	ADAPTER(12V DC 5 A)		